

HYDRAULIC SUBMERSIBLE DEWATERING PUMPS

GRIFFIN HYDRAULIC SUBMERSIBLE PUMPS ARE AVAILABLE IN 3 MODELS TO FIT YOUR PROJECT NEEDS.



- › Designed to handle high volumes of water, sludge, trash, raw sewage, and industrial effluent
- › Sizes range from 4"-24" with a variety of impeller designs
- › Pumps capable of 140 ft. of head and 20,000 GPM
- › Griffin has a variety of hydraulic power units to be used with hydraulic submersible pump-heads

- › **STAINLESS STEEL - RESISTS CORROSION**
- › **TRASH IMPELLERS HANDLE SOLIDS UP TO 3"**
- › **6MH/MHL MODELS FIT STANDARD MANHOLES**

TRASH PUMPS

- › Standard Manholes
- › Sewer Bypass Operations
- › Heavy Trash & Solids



MATERIAL HANDLING

- › Standard Manholes
- › Sewer Bypass Operations
- › Heavy Trash & Solids



AXIAL FLOW

- › High Flow Projects
- › River Bypass
- › Dam Repairs



	MAX CAPACITY (GPM)	MAX HEAD (FT.)
6T	990	72'
6THL	2000	140'
8T	1490	80'
10T	3450	94'
12T	5000	55'

	MAX CAPACITY (GPM)	MAX HEAD (FT.)
4MH	455	59'
4MHL	900	112'
6MH	1500	80'
6MHL	1800	119'

	MAX CAPACITY (GPM)	MAX HEAD (FT.)
24AX	20,000	35'

FOR MORE INFORMATION ON SALES & RENTALS CONTACT YOUR GROUNDWATER EXPERTS

GRIFFINGRIFFINDEWATERING.COM

1-800-431-1510